

TALUS

Ceiling Surface 

- Dimmable options.
- 2-3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux

Model (LED Power)**	Colour Temperature*	LED Lumen	CRI	Type	Beam Angle	Colour	Dimming Option***	Accessories
TALUS SURFACE 23.9W <i>(TALUS SF 24)</i>	[27B3621]	2700K - 3621lm	(80) 80	Fixed				ANTI-GLARE SHIELD [1X] White Matt [2X] Black Shiny [3X] Silver Shiny [4X] Gold Shiny ↓ [XX] EXTRAS [X0] No Extras
	[30B3847]	3000K - 3847lm						
	[40B3960]	4000K - 3960lm						
	[57B3847]	5700K - 3847lm						
TALUS PENDANT 23.9W <i>(TALUS PD 24)</i>	[27B2987]	2700K - 2987lm	(90) 90	Fixed	[20] 20°	[WH] White [BL] Black	[00] Without Driver	
	[30B3123]	3000K - 3123lm			[35] 35°		[ND] Non Dimmable	
	[40B3304]	4000K - 3304lm			[60] 60°		[A1] Analogue (1..10V)	
					[DX] DMX			
TALUS SURFACE 31.3W <i>(TALUS SF 31)</i>	[27B4510]	2700K - 4510lm	(80) 80	Fixed			[DL] DALI	
	[30B4792]	3000K - 4792lm					[PC] Phase Cut (Trailing Edge Dimmer)	
	[40B4933]	4000K - 4933lm						
	[57B4792]	5700K - 4792lm						
TALUS PENDANT 31.3W <i>(TALUS PD 31)</i>	[27B3721]	2700K - 3721lm	(90) 90	Fixed				
	[30B3890]	3000K - 3890lm						
	[40B4115]	4000K - 4115lm						


* Models with CCTs of 3500K, 5000K & 6500K are available upon request.

** In 31W models the driver must be externally installed.

*** DMX drivers must be externally installed for all models (24W & 31W).

Ordering Code Example:

TALUS SF 31-4QB4115-90-FX-35-WH-DX-20



Anti-glare Shield Accessories



Pendant model





Ceiling Surface

- Dimmable options.
- 2-3 SDCM
- L90/B10 50.000h



TUNABLE WHITE
2700K-----5000K

TALUS TUNABLE WHITE



LIGHTSOURCE BY
bridgelux


Model (LED Power)*	Colour Temperature	LED Lumen	CRI	Type	Beam Angle	Colour	Dimming Option**	Accessories
TALUS TW SURFACE 23.9W (TALUS TW SF 24)	(TWB2252) Tunable White 2700K-5000K 2252lm (Both CCTs driven)	(90) 90	[FX] Fixed	[20] 20° [35] 35° [60] 60°	[WH] White [BL] Black	[00] Without Driver [DX] DMX [DL] DALI	ANTI-GLARE SHIELD (1X) White Matt (2X) Black Shiny (3X) Silver Shiny (4X) Gold Shiny ↓ [XX] EXTRAS [X0] No Extras	
TALUS TW PENDANT 23.9W (TALUS TW PD 24)								
TALUS TW SURFACE 34.8W (TALUS TW SF 35)	(TWB3188) Tunable White 2700K-5000K 3188lm (Both CCTs driven)							
TALUS TW PENDANT 34.8W (TALUS TW PD 35)								

* In 35W models the driver must be externally installed.

** DMX drivers must be externally installed for all models (24W & 35W).

Ordering Code Example:

TALUS TW SF 35-TWB3188-90-FX-35-WH-DL-20



Anti-glare Shield Accessories



Pendant model



TALUS WD

Ceiling Surface 

- Dimmable options.
- 2-3 SDCM
- L70/B50 50.000h





Warm Dimming **3000K to 1800K**

LIGHTSOURCE BY
bridgelux

Model (LED Power)	Colour Temperature	LED Lumen	CRI	Type	Beam Angle	Colour	Dimming Option	Accessories
TALUS WD SURFACE 30.7W <i>(TALUS WD SF 31)</i>	1800K-3000K 2840lm	2840lm	(95) 95	Fixed	(20) 20° (35) 35° (60) 60°	(WH) White (BL) Black	(00) Without Driver (A1) Analogue (1..10V) (DX) DMX (DL) DALI (PC) Phase Cut (Trailing Edge Dimmer)	ANTI-GLARE SHIELD (1X) White Matt (2X) Black Shiny (3X) Silver Shiny (4X) Gold Shiny ↓ (XX) EXTRAS (X0) No Extras
TALUS WD PENDANT 30.7W <i>(TALUS WD PD 31)</i>								

Ordering Code Example:
TALUS WD SF 31-1830B2840-95-FX-20-BL-PC-10

Warm dimming 3000K to 1800K



Anti-glare Shield Accessories



Pendant model

