

TALUS ADJ Recessed

Ceiling Recessed 

- Dimmable options.
- 2-3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux

Model (LED Power)	Colour Temperature*	LED Lumen	CRI	Type	Beam Angle	Colour	Dimming Option
TALUS Adjustable Recessed 23.9W (TALUS A RC24)	(27B3621)	2700K - 3621lm	[80] 80	Adjustable	[20] 20° [38] 38° [60] 60° [110] 110°	[WH] White [BL] Black	[00] Without Driver [ND] Non Dimmable [A1] Analogue (1..10V) [DX] DMX [DL] DALI [PB] Push Button [PC] Phase Cut (Trailing Edge Dimmer)
	(30B3847)	3000K - 3847lm					
	(40B3960)	4000K - 3960lm					
	(57B3847)	5700K - 3847lm	[90] 90				
	(27B2987)	2700K - 2987lm					
	(30B3123)	3000K - 3123lm					
	(40B3304)	4000K - 3304lm	[97] 97				
	(27B2647)	2700K - 2647lm					
	(30B2829)	3000K - 2829lm					
TALUS Adjustable Recessed 31.3W (TALUS A RC31)	(27B4510)	2700K - 4510lm	[80] 80	Adjustable	[20] 20° [38] 38° [60] 60° [110] 110°	[WH] White [BL] Black	[00] Without Driver [ND] Non Dimmable [A1] Analogue (1..10V) [DX] DMX [DL] DALI [PB] Push Button [PC] Phase Cut (Trailing Edge Dimmer)
	(30B4792)	3000K - 4792lm					
	(40B4933)	4000K - 4933lm					
	(57B4792)	5700K - 4792lm	[90] 90				
	(27B3721)	2700K - 3721lm					
	(30B3890)	3000K - 3890lm					
	(40B4115)	4000K - 4115lm	[97] 97				
	(27B3298)	2700K - 3298lm					
	(30B3524)	3000K - 3524lm					
TALUS Adjustable Recessed 37.1W (TALUS A RC37)	(27B5199)	2700K - 5199lm	[80] 80	Adjustable	[20] 20° [38] 38° [60] 60° [110] 110°	[WH] White [BL] Black	[00] Without Driver [ND] Non Dimmable [A1] Analogue (1..10V) [DX] DMX [DL] DALI [PB] Push Button [PC] Phase Cut (Trailing Edge Dimmer)
	(30B5524)	3000K - 5524lm					
	(40B5687)	4000K - 5687lm					
	(57B5524)	5700K - 5524lm	[90] 90				
	(27B4289)	2700K - 4289lm					
	(30B4484)	3000K - 4484lm					
	(40B4744)	4000K - 4744lm	[97] 97				
	(27B3802)	2700K - 3802lm					
	(30B4062)	3000K - 4062lm					

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.

Ordering Code Example:

TALUS A RC31-30B4792-80-AD-38-WH-DX

